



TRITON LED LOW BAY

PID: SL913LB4, SL913LB6



SL913LB6



SL913LB4



APPLICATIONS:

- WORKSHOPS
- WAREHOUSES
- SUPERMARKETS
- MANUFACTURING FACILITIES

SPECIFICATIONS:

FEATURES

Die-formed heavy gauge cold rolled steel for durability

Baked white enamel for premium lumen output

Perfect for maintaining continuous lighting in indoor facilities

Compatible with T8 and LED X series tubes (sold separately)

ENERGY DATA

Driver: 100-277V

Power factor >0.90

MOUNTING

Surface, suspended or chain mountable

Suspended mounting (V-hooks included)

G13/Bi-pin tombstones for Straits Lighting 4ft LED T8 lamps

CERTIFICATIONS

UL / cUL certified

IFAR Standard listed

WARRANTY

5 year warranty

PRODUCT DETAILS

Lamps Capacity	Tube Capacity	Length	Input	Base
LB4 (4) 4' T8 Lamps	4 Lamps	48"	100-277V	G13
LB6 (6) 4' T8 Lamps	6 Lamps	48"	100-277V	G13

PRODUCT DIMENSIONS

Product	Length (Inches)	Width (Inches)	Height (Inches)
LB4	48.6	11.75	3.87
LB6	48.6	16.3	3.87

ORDER CODE

ORDER CODE	LENGTH	Base/Mount
SL913LB4 SL913LB6	4 = 4'	G13

ORDER EXAMPLE: SL913LB4 - 4 - G13