

LED IN-LINE VAPOR-TIGHT FIXTURE

PID: SL913INL



APPLICATIONS:

- DUSTY/WET ENVIRONMENTS
- FARMYARDS
- PARKING GARAGES
- MANUFACTURING FACILITIES
- WATER/DUST/WEATHER RESISTANT

SPECIFICATIONS:

FEATURES

- 100% UV Stabilized Polycarbonate
- Silicone Gasket Perimeter
- Clear Polycarbonate Lens
- Weather resistant and no parts are left exposed to corrosion
- 4ft model uses TWO 4ft LED Lamps (sold separately)
- 2ft model uses TWO 2ft LED Lamps (sold separately)

MOUNTING

- Stainless Steel Mounting Bracket
- Surface or Suspended
- G13 Tombstones for Straits Lighting LED T8 Tubes
- Single ended

CERTIFICATIONS


- Listed for IFAR Standard
- IP65

WARRANTY

- 5 year warranty

PRODUCT DIMENSIONS

PRODUCT	Width (In)	Length (In)	Height (Inch)
SL913INL-.5X2	5 ½	26 ⅞	3 ½
SL913INL-.5X4	5 ½	50 ⅞	4 ⅜



ORDERING GUIDE

ORDER CODE	LENGTH	FIXTURE LENS	BASE/MOUNT
SL913INL	.5x2 = .5'x2' .5x4 = .5'x4'	C = Clear	G13 = G13

ORDER EXAMPLE: SL913INL-.5x4-C-G13