



## STRAITS LED UTILITY LIGHT

PID: SL925SL



### EASY INSTALLATION

#### APPLICATIONS:

- WORKSHOPS
- RETAIL & COMMERCIAL AREAS
- SUPERMARKETS
- GARAGES
- STORAGE AREAS
- WORK BENCH

### SPECIFICATIONS:

#### FEATURES

- Steel reflector & Optical polycarbonate diffuser
- 5.5 ft power cord with pull chain ON/OFF
- Min starting temperature -4°F (-20°C)
- Max starting temperature 113°F (45°C)

#### ENERGY DATA

- Driver: 100-277V
- Power factor ≥ 0.90
- THD < 20%

#### LED MODULES

- Available Kelvin temperature of 50K
- Beam angle: 155°
- CRI ≥ 80
- 50,000 hour rated life

#### MOUNTING

- Pendant or chain mountable
- Direct wiring optional

#### CERTIFICATIONS

- UL / cUL certified
- IP20 rated
- FCC certified

#### WARRANTY

- 5 year warranty

### PRODUCT DETAILS

Product	Kelvin	Input	Length	Beam Angle	Lumens	Efficacy	Replacement
38W	5000K	120V	48"	155°	4,000	105	100W FL

## BOX DIMENSIONS

---

Product	Length (Inches)	Width (Inches)	Height (Inches)
38W	49	10.4	15

## ORDER CODE

---

ORDER CODE	WATTS	Input
SL925SL	38W	120

ORDER EXAMPLE: SL925SL - 38W - 120