



SPECIFICATION FEATURES

OPTICS

- ◆ Lens options: Frosted
- ◆ 120° beam angle

MOUNTING

- ◆ Suspended cable mounting (kit included w/cables)
- ◆ Recessed drop ceiling mount
- ◆ Wall mount/ Flush mount
- ◆ Hurricane clips included

WARRANTY

- ◆ **Five** year warranty

LED MODULES

- ◆ Each LED module contains SMD 5630 or 3014 LEDs
- ◆ Color temperature of 3000-5000 Kelvin
- ◆ Mercury free
- ◆ 50,000 hour rated life
- ◆ Dimmable (0-10V)

CONSTRUCTION

- ◆ Sizes:
 - 2'x2'
 - 2'x4'
- ◆ External driver
- ◆ Aluminum suspended cable mounting brackets
- ◆ Aluminum casing
- ◆ Plastic lens (Frosted)
- ◆ High shock and vibrant resistant
- ◆ For indoor use only

FINISH

- ◆ Polyester powder paint used for all die-cast components
- ◆ Frosted surface lens
- ◆ White trim

Product #	SL917SS / SL917SR
Project	
Comments	
Prepared By	
Date	

ENERGY DATA

- ◆ Electronic LED Driver
- ◆ Power Factor > 0.9
- ◆ Total Harmonic Distortion < 20%
- ◆ 100-277 VAC
- ◆ 50/60 HZ
- ◆ -20°C Min. Temperature
- ◆ 50°C Max. Temperature

CERTIFICATION DATA

- ◆ DLC Premium Qualified Product List
- ◆ UL Certified



PRODUCT DETAILS

SLIM LED FLAT PANEL

Product Code	Input (VAC)	Wattage (W)	CCT ¹ (K)	Beam Angle	Initial Lumens (lm)	Efficacy	Rated Life ^{2,3} (hrs)	CRI	Dimmable	Certificate
SL917SS-2x2-30W	100-277V	30	3000-5000	120	3900	130	50,000	>80	Yes	UL/cUL
SL917SS-2x2-40W	100-277V	40	3000-5000	120	5000	125	50,000	>80	Yes	UL/cUL
SL917SR-2x4-40W	100-277V	40	3000-5000	120	5000	125	50,000	>80	Yes	UL/cUL
SL917SR-2x4-50W	100-277V	50	3000-5000	120	6250	126	50,000	>80	Yes	UL/cUL
SL917SR-2x4-75W	100-277V	75	3000-5000	120	8600	115	50,000	>80	Yes	UL/cUL

1. CCT range complies to ANSI C78.377-2008
2. Rated average life based on engineering testing and probability analysis
3. Lifetime test consistent with IESNA LM80 lumen maintenance procedure

ORDERING INFORMATION

SAMPLE NUMBER: SL917SS-2x2-40W-100/277V-4000-F-120-E-D

			100/277V		F	120	E	D
Category SL917SS = Slim Square (2x2) SL917SR = Slim Rectangle (2x4)	Length 2x2 = 2'x2' 2x4 = 2'x4'	Wattage 30W = 30W 40W = 40W 50W = 50W 75W = 75W	Voltage 100/277V = 100~277V	CCT 3000 = 3000K 4000 = 4000K 5000 = 5000K	Lens (Fixture) F = Frosted	Beam Angle 120 = 120°	Driver E = External	Dimming D = Dimming

- ◆ SL917SS-2x2-30W; SL917SR-2x4-40W; SL917SR-2x4-75W or units in 3000K must be special ordered. Contact for lead times.

CONTACT US

Phone: (855) TSLC - LED
(855) 875 - 2533
Fax: (248) 671 - 0624

Address:
12501 E. Grand River Ave.
Suite 200
Brighton, MI 48116



The Straits Lighting Company is constantly developing and improving its products. For this reason, all product descriptions in this brochure are intended as a general guide, and we may change specifications from time to time in the interest of product development, without prior notification or public announcement. All descriptions in this publication present only general particulars of the goods to which they refer and shall not form part of any contract. Data in this guide has been obtained in controlled experimental conditions. However, The Straits Lighting Company cannot accept any liability arising from the reliance on such data to the extent permitted.