

LIGHTHOUSE LED HANGING HIGH BAY

Temporary work light

PID: SL915WLC (Frosted Lens)



APPLICATIONS:

- CONSTRUCTION ZONES
- GARAGES
- WAREHOUSES
- FACTORIES

SPECIFICATIONS:

FEATURES

- Stainless steel wire guard for impact protection
- Suitable for indoor and outdoor use
- Linkable fixture connection
- Operating temperature -40°F to 113°F (-40°C to 45°C)
- 10 Foot wire cord

ENERGY DATA

- Driver: 100-277V
- Power Factor >0.90
- 6KVA surge protection

LED MODULES

- 50,000 hour rated life
- Available color temperature of 50K
- Beam angle: 320°
- CRI ≥ 80

ADD ONS

- Microwave sensor
- Extension cord

MOUNTING

- Bracket mounting

CERTIFICATIONS

- IP64 Rated
- UL certified

WARRANTY

- 5 year warranty

PRODUCT DETAILS

Product	Input (VAC)	Lumens	Efficacy	CCT ¹	Beam Angle	Rated Life (hours)
40W	100-277V	5,000	125	5000K	320°	50,000
60W	100-277V	7,500	125	5000K	320°	50,000
80W	100-277V	10,000	125	5000K	320°	50,000
100W	100-277V	12,500	125	5000K	320°	50,000
120W	100-277V	15,000	125	5000K	320°	50,000

ORDERING GUIDE

ORDER CODE	WATTS	VOLTS	KELVIN	LENS
SL915WLC	40W, 60W 80W, 100W, 120W	SU = 100-277V	50K = 5000K	F = Frosted

ORDER EXAMPLE: SL915WLC - 40W - SU - 50K - F

PRODUCT DIMENSIONS



Watts	Length (Inches)	Height (Inches)
40W, 60W	6.9"	12"
80W, 100W	6.9"	12.6"
120W	6.9"	14.8"

LM79 REPORT

Light Distribution

