

DESCRIPTION

Combined with high-efficiency light engine, this LED wall pack features a high-quality UV-resistant PC lens, which provides excellent lighting.

SPECIFICATION FEATURES

CONSTRUCTION

- Sealed die-casting profile for outdoor applications.
- Casting thermally conducts LED heat to optimize performance and long life.
- Suitable for applications requiring 3G testing prescribed by ANSI C136.31.

OPTICS

- UV stabilized polycarbonate optic lens, the professional prismatic design offers a good light distribution control and guarantees the uniformity.

ELECTRICAL

- Universal 120-277 VAC input voltage.
- 1-10V Dimming.
- Drivers have a power factor >90%, THD <20%.
- Operating Temperature Range: -40°C to 40°C (-40°F - + 104°F).

Note: Operating with emergency battery temperature range: 10°C to 40°C (+50°F - + 104°F).

LIFESPAN

- 50,000 hours rated life

WARRANTY

- Five-year warranty.

CERTIFICATIONS

- UL wet location listed.
- DLC qualified.

NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C(±5°C) specifications subject to change without notice.

PERFORMANCE DATA


SYSTEM WATTS	VOLTAGE	CRI	LUMENS (4000K)	LPW (4000K)	LUMENS (5000K)	LPW (5000K)
125W	120-277VAC	70	15000lm	120 lm/W	15000lm	120 lm/W

ELECTRICAL DATA

Number Of Drivers	Driver Current (mA)	Nominal Power (W)	INPUT VOLTAGE (V)	CURRENT (Amps)
2	3300	125	120	1.04
		125	208	0.60
		125	240	0.52
		125	277	0.45



PHOTOMETRICS



ACCESSORIES



Photocell



USE: Photocell is field installed or pre-installed by requesting



Emergency Battery Backup

USE: It can be pre-installed or field installed. Only suitable for 30W,40W,65W,90W,100W.

DIMENSIONS UNIT: MM/INCH



Net Weight
125W: 8.157lb